



# Filtration

## ES Compleat PG Premix

### Cummins Filtration

Catalogue number: CC2835, CC2836, CC2837, CC2838, CC2850  
Version No: 1.3  
Safety Data Sheet

Issue Date: 03/07/2018  
Print Date: 03/07/2018  
S.GHS.CAN.EN

## SECTION 1 IDENTIFICATION

### Product Identifier

|                               |                                                                                                                                                                                 |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name                  | ES Compleat PG Premix                                                                                                                                                           |
| Synonyms                      | CC2835 (1 gallon / 3.785 L of 50/50), CC2836 (55 gallon / 208 L of 50/50), CC2837 (Bulk of 50/50), CC2850 (5 gallon / 18.9 L of 50/50), CC2838 (275 gallon / 1040 L Tote tanks) |
| Other means of identification | Not Available                                                                                                                                                                   |

### Recommended use of the chemical and restrictions on use

|                          |                                                                        |
|--------------------------|------------------------------------------------------------------------|
| Relevant identified uses | extended life coolant, especially for use in heavy-duty diesel engines |
|--------------------------|------------------------------------------------------------------------|

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

|                         |                                                |
|-------------------------|------------------------------------------------|
| Registered company name | Cummins Filtration                             |
| Address                 | 1200 Fleetguard Rd Cookeville TN United States |
| Telephone               | 1-800-223-4583                                 |
| Fax                     | Not Available                                  |
| Website                 | www.cumminsfiltration.com                      |
| Email                   | fleetmaster.us@cummins.com                     |

### Emergency phone number

|                                   |                 |
|-----------------------------------|-----------------|
| Association / Organisation        | Chemtrec        |
| Emergency telephone numbers       | 1-800-424-9300  |
| Other emergency telephone numbers | +1-703-527-3887 |

## SECTION 2 HAZARD(S) IDENTIFICATION

### Classification of the substance or mixture

|                |                            |
|----------------|----------------------------|
| Classification | Eye Irritation Category 2B |
|----------------|----------------------------|

### Label elements

|                     |                |
|---------------------|----------------|
| Hazard pictogram(s) | Not Applicable |
|---------------------|----------------|

|             |                |
|-------------|----------------|
| SIGNAL WORD | <b>WARNING</b> |
|-------------|----------------|

### Hazard statement(s)

|      |                        |
|------|------------------------|
| H320 | Causes eye irritation. |
|------|------------------------|

### Hazard(s) not otherwise specified

Not Applicable

### Precautionary statement(s) Prevention

|      |                                                                 |
|------|-----------------------------------------------------------------|
| P264 | Wash all exposed external body areas thoroughly after handling. |
|------|-----------------------------------------------------------------|

### Precautionary statement(s) Response

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337+P313      | If eye irritation persists: Get medical advice/attention.                                                                        |

Continued...

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

Not Applicable

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No    | %[weight] | Name                                                                      |
|-----------|-----------|---------------------------------------------------------------------------|
| 57-55-6   | 40-55     | <u>propylene glycol</u>                                                   |
| 7632-00-0 | 0.1-0.3   | <u>sodium nitrite</u>                                                     |
| 1330-43-4 | 0.1-0.2   | <u>sodium borate anhydrous (Na<sub>2</sub>B<sub>4</sub>O<sub>7</sub>)</u> |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4 FIRST-AID MEASURES****Description of first aid measures**

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>                                            |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>                                                                                                                                                                                                                                                                                              |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>       |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul> |

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

- ▶ Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- ▶ Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- ▶ Treatment consists of supportive care.

*[Ellenhorn and Barceloux: Medical Toxicology]*

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

- ▶ The usual measures are supportive care and decontamination (Ipecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
- ▶ Check the anion gap, arterial pH, renal function and glucose levels.

*Ellenhorn and Barceloux: Medical Toxicology***SECTION 5 FIRE-FIGHTING MEASURES****Extinguishing media**

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

- ▶ foam.
- ▶ dry chemical powder.
- ▶ carbon dioxide.

**Special hazards arising from the substrate or mixture**

|                             |             |
|-----------------------------|-------------|
| <b>Fire Incompatibility</b> | None known. |
|-----------------------------|-------------|

**Special protective equipment and precautions for fire-fighters**

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>                                                      |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ The material is not readily combustible under normal conditions.</li> <li>▶ However, it will break down under fire conditions and the organic component may burn.</li> <li>▶ Not considered to be a significant fire risk.</li> <li>▶ Heat may cause expansion or decomposition with violent rupture of containers.</li> <li>▶ Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> </ul> <p>Decomposes on heating and produces toxic fumes of:<br/>carbon dioxide (CO<sub>2</sub>)<br/>other pyrolysis products typical of burning organic material.<br/>May emit poisonous fumes.<br/>May emit corrosive fumes.</p> |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Major Spills</b> | <p>Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT allow material to contact humans, exposed food or food utensils.</b></li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul> |
| <b>Other information</b> | <p>Consider storage under inert gas.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

### Conditions for safe storage, including any incompatibilities

|                           |                                                                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable container</b> | <ul style="list-style-type: none"> <li>▶ Polyethylene or polypropylene container.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Storage incompatibility**

- ▶ Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.
- Alcohols
  - ▶ are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
  - ▶ reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
  - ▶ react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
  - ▶ should not be heated above 49 deg. C. when in contact with aluminium equipment

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

| Source                                                                                  | Ingredient                                                               | Material name                                      | TWA                                | STEL                | Peak          | Notes                                         |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------|----------------------------------------------------|------------------------------------|---------------------|---------------|-----------------------------------------------|
| Canada - Ontario Occupational Exposure Limits                                           | propylene glycol                                                         | 1,2-Propylene glycol                               | 155; 10 mg/m <sup>3</sup> / 50 ppm | Not Available       | Not Available | Not Available                                 |
| Canada - Nova Scotia Occupational Exposure Limits                                       | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium tetraborate - Anhydrous                     | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | TLV Basis: upper respiratory tract irritation |
| Canada - Nova Scotia Occupational Exposure Limits                                       | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium tetraborate - Pentahydrate                  | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | TLV Basis: upper respiratory tract irritation |
| Canada - Nova Scotia Occupational Exposure Limits                                       | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium tetraborate - Decahydrate                   | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | TLV Basis: upper respiratory tract irritation |
| Canada - Alberta Occupational Exposure Limits                                           | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borates, tetra, sodium salts, Decahydrate          | 1 mg/m <sup>3</sup>                | 3 ppm               | Not Available | Not Available                                 |
| Canada - Alberta Occupational Exposure Limits                                           | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borates, tetra, sodium salts, Anhydrous            | 1 mg/m <sup>3</sup>                | 3 ppm               | Not Available | Not Available                                 |
| Canada - Alberta Occupational Exposure Limits                                           | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borates, tetra, sodium salts, Pentahydrate         | 1 mg/m <sup>3</sup>                | 3 ppm               | Not Available | Not Available                                 |
| Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borate compounds, inorganic (inhalable fraction++) | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | Not Available                                 |
| Canada - Manitoba Occupational Exposure Limits                                          | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Not Available                                      | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | Not Available                                 |
| Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)         | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium tetraborate, decahydrate or borax           | 5 mg/m <sup>3</sup>                | Not Available       | Not Available | Not Available                                 |
| Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)         | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium tetraborate, anhydre                        | 1 mg/m <sup>3</sup>                | Not Available       | Not Available | Not Available                                 |
| Canada - Northwest Territories Occupational Exposure Limits (English)                   | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borate compounds, inorganic (inhalable fraction)   | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | Not Available                                 |
| Canada - British Columbia Occupational Exposure Limits                                  | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borate compounds, Inorganic, Inhalable             | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | Not Available                                 |
| Canada - Prince Edward Island Occupational Exposure Limits                              | sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Borate compounds, inorganic                        | 2 mg/m <sup>3</sup>                | 6 mg/m <sup>3</sup> | Not Available | TLV® Basis: URT irr                           |

**EMERGENCY LIMITS**

| Ingredient                                                               | Material name                         | TEEL-1                | TEEL-2                  | TEEL-3                  |
|--------------------------------------------------------------------------|---------------------------------------|-----------------------|-------------------------|-------------------------|
| propylene glycol                                                         | Propylene glycol; (1,2-Propanediol)   | 30 mg/m <sup>3</sup>  | 1,300 mg/m <sup>3</sup> | 7,900 mg/m <sup>3</sup> |
| sodium nitrite                                                           | Sodium nitrite                        | 6.4 mg/m <sup>3</sup> | 71 mg/m <sup>3</sup>    | 240 mg/m <sup>3</sup>   |
| sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium borate decahydrate (Borax)     | 6 mg/m <sup>3</sup>   | 190 mg/m <sup>3</sup>   | 1,100 mg/m <sup>3</sup> |
| sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Sodium borate; (Disodium tetraborate) | 6 mg/m <sup>3</sup>   | 88 mg/m <sup>3</sup>    | 530 mg/m <sup>3</sup>   |

  

| Ingredient                                                               | Original IDLH | Revised IDLH  |
|--------------------------------------------------------------------------|---------------|---------------|
| propylene glycol                                                         | Not Available | Not Available |
| sodium nitrite                                                           | Not Available | Not Available |
| sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | Not Available | Not Available |

**Exposure controls****Appropriate engineering controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and

"removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.  
Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant:                                                                                                                                                                                                | Air Speed:                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air).                                                                                                                                            | 0.25-0.5 m/s (50-100 f/min)  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)   |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)                                                      | 1-2.5 m/s (200-500 f/min.)   |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)                                                                 | 2.5-10 m/s (500-2000 f/min.) |

Within each range the appropriate value depends on:

| Lower end of the range                                     | Upper end of the range           |
|------------------------------------------------------------|----------------------------------|
| 1: Room air currents minimal or favourable to capture      | 1: Disturbing room air currents  |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production.                           | 3: High production, heavy use    |
| 4: Large hood or large air mass in motion                  | 4: Small hood-local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

#### Personal protection



#### Eye and face protection

- ▶ Safety glasses with side shields.
- ▶ Chemical goggles.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

#### Skin protection

See Hand protection below

#### Hands/feet protection

- ▶ Wear chemical protective gloves, e.g. PVC.
  - ▶ Wear safety footwear or safety gumboots, e.g. Rubber
- The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
- Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
- frequency and duration of contact,
  - chemical resistance of glove material,
  - glove thickness and
  - dexterity
- Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
  - When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
  - Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
  - Contaminated gloves should be replaced.
- For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
- It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
- Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
- Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
  - Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential
- Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is

|                         |                                                                                                                                                                             |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                         | recommended.                                                                                                                                                                |
| <b>Body protection</b>  | See Other protection below                                                                                                                                                  |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C. apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul> |
| <b>Thermal hazards</b>  | Not Available                                                                                                                                                               |

### Respiratory protection

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--------------------------------------------------------------------|----------------------|----------------------|
| up to 10                           | 1000                                                               | A-AUS / Class 1      | -                    |
| up to 50                           | 1000                                                               | -                    | A-AUS / Class 1      |
| up to 50                           | 5000                                                               | Airline *            | -                    |
| up to 100                          | 5000                                                               | -                    | A-2                  |
| up to 100                          | 10000                                                              | -                    | A-3                  |
| 100+                               |                                                                    | -                    | Airline**            |

\* - Continuous Flow

\*\* - Continuous-flow or positive pressure demand.

A(All classes) = Organic vapours, B AUS or B1 = Acid gases, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deg C)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                                                     |                   |                                                |               |
|-----------------------------------------------------|-------------------|------------------------------------------------|---------------|
| <b>Appearance</b>                                   | Clear Blue Liquid |                                                |               |
| <b>Physical state</b>                               | Liquid            | <b>Relative density (Water = 1)</b>            | 1.03-1.06     |
| <b>Odour</b>                                        | Not Available     | <b>Partition coefficient n-octanol / water</b> | Not Available |
| <b>Odour threshold</b>                              | Not Available     | <b>Auto-ignition temperature (°C)</b>          | Not Available |
| <b>pH (as supplied)</b>                             | 10.2-10.8         | <b>Decomposition temperature</b>               | Not Available |
| <b>Melting point / freezing point (°C)</b>          | Not Available     | <b>Viscosity (cSt)</b>                         | Not Available |
| <b>Initial boiling point and boiling range (°C)</b> | 106               | <b>Molecular weight (g/mol)</b>                | Not Available |
| <b>Flash point (°C)</b>                             | Not Available     | <b>Taste</b>                                   | Not Available |
| <b>Evaporation rate</b>                             | Not Available     | <b>Explosive properties</b>                    | Not Available |
| <b>Flammability</b>                                 | Not Available     | <b>Oxidising properties</b>                    | Not Available |
| <b>Upper Explosive Limit (%)</b>                    | Not Available     | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available |
| <b>Lower Explosive Limit (%)</b>                    | Not Available     | <b>Volatile Component (%vol)</b>               | Not Available |
| <b>Vapour pressure (kPa)</b>                        | Not Available     | <b>Gas group</b>                               | Not Available |
| <b>Solubility in water (g/L)</b>                    | Miscible          | <b>pH as a solution (1%)</b>                   | Not Available |
| <b>Vapour density (Air = 1)</b>                     | Not Available     | <b>VOC g/L</b>                                 | Not Available |

## SECTION 10 STABILITY AND REACTIVITY

|                                           |                                                                                                                                                                                                      |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                         | See section 7                                                                                                                                                                                        |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7                                                                                                                                                                                        |
| <b>Conditions to avoid</b>                | See section 7                                                                                                                                                                                        |
| <b>Incompatible materials</b>             | See section 7                                                                                                                                                                                        |
| <b>Hazardous decomposition products</b>   | See section 5                                                                                                                                                                                        |

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhaled</b> | The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow. |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## ES Compleat PG Premix

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                     | Inhalation hazard is increased at higher temperatures.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Ingestion</b>    | <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation.</p> <p>Excessive repeated ingestions may cause hypoglycaemia (low levels of glucose in the blood stream) among susceptible individuals; this may result in muscular weakness, incoordination and mental confusion.</p> <p>Very high doses given during feeding studies to rats and dogs produce central nervous system depression (although one-third of that produced by ethanol), haemolysis and insignificant kidney changes.</p> <p>In humans propylene glycol is partly excreted unchanged in the urine and partly metabolised as lactic and pyruvic acid. Lactic acidosis may result.</p> <p>If swallowed, the toxic effects of glycols (dihydric alcohols) are similar to those of alcohol, with depression of the central nervous system, nausea, vomiting, and degenerative changes in the liver and kidney.</p> <p>Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma.</p> |
| <b>Skin Contact</b> | <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>A single prolonged exposure is not likely to result in the material causing harm. However, when applied in large quantities to damaged skin as a topical preparation or by contact with clothing accidentally contaminated by the material, there may be the potential to absorb the material in harmful amounts.</p> <p>Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>                                                             |
| <b>Eye</b>          | <p>Irritation of the eyes may produce a heavy secretion of tears (lachrymation).</p> <p>Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Chronic</b>      | <p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                                          |                                                      |                                    |
|------------------------------------------|------------------------------------------------------|------------------------------------|
| <b>ES Compleat PG Premix</b>             | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                                          | Not Available                                        | Not Available                      |
| <b>propylene glycol</b>                  | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                                          | Dermal (rabbit) LD50: 11890 mg/kg <sup>[2]</sup>     | Eye (rabbit): 100 mg - mild        |
|                                          | Oral (rat) LD50: 20000 mg/kg <sup>[2]</sup>          | Eye (rabbit): 500 mg/24h - mild    |
|                                          |                                                      | Skin(human):104 mg/3d Intermit Mod |
|                                          |                                                      | Skin(human):500 mg/7days mild      |
| <b>sodium nitrite</b>                    | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                                          | Inhalation (rat) LC50: 0.0055 mg/l/4H <sup>[2]</sup> | Eye (rabbit): 500 mg/24hr - mild   |
|                                          | Oral (rat) LD50: 157.9 mg/kg <sup>[2]</sup>          |                                    |
| <b>sodium borate anhydrous (Na2B4O7)</b> | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                                          | Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>     | Not Available                      |
|                                          | Oral (rat) LD50: >250 mg/kg <sup>[1]</sup>           |                                    |

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SODIUM NITRITE</b>                    | <p>The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>Tumorigenic - Carcinogenic by RTECS criteria.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>SODIUM BORATE ANHYDROUS (NA2B4O7)</b> | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p> <p>Reproductive effector in rats Mutagenic towards bacteria</p> |

|                                          |   |                                 |   |
|------------------------------------------|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ☐ | <b>Carcinogenicity</b>          | ☐ |
| <b>Skin Irritation/Corrosion</b>         | ☐ | <b>Reproductivity</b>           | ☐ |
| <b>Serious Eye Damage/Irritation</b>     | ☑ | <b>STOT - Single Exposure</b>   | ☐ |
| <b>Respiratory or Skin sensitisation</b> | ☐ | <b>STOT - Repeated Exposure</b> | ☐ |

Mutagenicity



Aspiration Hazard



Legend: - Data available but does not fill the criteria for classification  
 - Data available to make classification  
 - Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| ES Compleat PG Premix | ENDPOINT      | TEST DURATION (HR) | SPECIES       | VALUE         | SOURCE        |
|-----------------------|---------------|--------------------|---------------|---------------|---------------|
|                       | Not Available | Not Available      | Not Available | Not Available | Not Available |

  

| propylene glycol | ENDPOINT | TEST DURATION (HR) | SPECIES                       | VALUE     | SOURCE |
|------------------|----------|--------------------|-------------------------------|-----------|--------|
|                  | LC50     | 96                 | Fish                          | 710mg/L   | 4      |
|                  | EC50     | 48                 | Crustacea                     | >1000mg/L | 4      |
|                  | EC50     | 96                 | Algae or other aquatic plants | 19000mg/L | 2      |
|                  | NOEC     | 168                | Fish                          | 98mg/L    | 4      |

  

| sodium nitrite | ENDPOINT | TEST DURATION (HR) | SPECIES                       | VALUE          | SOURCE |
|----------------|----------|--------------------|-------------------------------|----------------|--------|
|                | LC50     | 96                 | Fish                          | 0.048mg/L      | 4      |
|                | EC50     | 48                 | Crustacea                     | ca.12.5100mg/L | 1      |
|                | EC50     | 72                 | Algae or other aquatic plants | >100mg/L       | 2      |
|                | NOEC     | 2                  | Fish                          | 0.02mg/L       | 4      |

  

| sodium borate anhydrous (Na2B4O7) | ENDPOINT | TEST DURATION (HR) | SPECIES                       | VALUE     | SOURCE |
|-----------------------------------|----------|--------------------|-------------------------------|-----------|--------|
|                                   | LC50     | 96                 | Fish                          | 74mg/L    | 2      |
|                                   | EC50     | 96                 | Algae or other aquatic plants | 15.4mg/L  | 4      |
|                                   | NOEC     | 768                | Fish                          | 0.009mg/L | 2      |

## Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival. Large quantities of dissolved oxygen (DO) in the water column are consumed when microbial populations decompose propylene glycol. Sufficient dissolved oxygen levels in surface waters are critical for the survival of fish, macro-invertebrates, and other aquatic organisms. If oxygen concentrations drop below a minimum level, organisms emigrate, if able and possible, to areas with higher oxygen levels or eventually die. This effect can drastically reduce the amount of usable aquatic habitat. Reductions in DO levels can reduce or eliminate bottom-feeder populations, create conditions that favour a change in a community's species profile, or alter critical food-web interactions.

log Kow : -1.41 - 0.3  
 Half-life (hr) air : 32  
 Henry's atm m3/mol: 1.20E-08

BOD 5: 0.995, 2.2%

ThOD : 1.685

BCF : <1

Bioaccumulation : not sig

processes Abiotic: photoxid

**DO NOT discharge into sewer or waterways.**

## Persistence and degradability

| Ingredient       | Persistence: Water/Soil | Persistence: Air |
|------------------|-------------------------|------------------|
| propylene glycol | LOW                     | LOW              |
| sodium nitrite   | LOW                     | LOW              |

## Bioaccumulative potential

| Ingredient       | Bioaccumulation       |
|------------------|-----------------------|
| propylene glycol | LOW (BCF = 1)         |
| sodium nitrite   | LOW (LogKOW = 0.0564) |

## Mobility in soil

| Ingredient       | Mobility          |
|------------------|-------------------|
| propylene glycol | HIGH (KOC = 1)    |
| sodium nitrite   | LOW (KOC = 23.74) |

## SECTION 13 DISPOSAL CONSIDERATIONS

Continued...



**Waste treatment methods**

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product / Packaging disposal</b> | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

|                         |    |
|-------------------------|----|
| <b>Marine Pollutant</b> | NO |
|-------------------------|----|

**Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**PROPYLENE GLYCOL(57-55-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Canada - Ontario Occupational Exposure Limits

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

**SODIUM NITRITE(7632-00-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

**SODIUM BORATE ANHYDROUS (NA2B4O7)(1330-43-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Canada - Northwest Territories Occupational Exposure Limits (English)

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants (French)

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

| National Inventory            | Status                                                                                                                                                                                   |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Australia - AICS              | Y                                                                                                                                                                                        |
| Canada - DSL                  | Y                                                                                                                                                                                        |
| Canada - NDSL                 | N (propylene glycol; sodium borate anhydrous (Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ); sodium nitrite)                                                                           |
| China - IECSC                 | Y                                                                                                                                                                                        |
| Europe - EINEC / ELINCS / NLP | Y                                                                                                                                                                                        |
| Japan - ENCS                  | Y                                                                                                                                                                                        |
| Korea - KECI                  | Y                                                                                                                                                                                        |
| New Zealand - NZIoC           | Y                                                                                                                                                                                        |
| Philippines - PICCS           | Y                                                                                                                                                                                        |
| USA - TSCA                    | Y                                                                                                                                                                                        |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

**SECTION 16 OTHER INFORMATION****Other information**

## ES Compleat PG Premix

**Ingredients with multiple cas numbers**

| Name                                                                        | CAS No                           |
|-----------------------------------------------------------------------------|----------------------------------|
| sodium borate anhydrous<br>(Na <sub>2</sub> B <sub>4</sub> O <sub>7</sub> ) | 1330-43-4, 1303-96-4, 12179-04-3 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.