



# ES Compleat™ OAT

Nitrite, Amine, Phosphate & Silicate Free

## Proven Performance:

- Life-of-the-Engine, 1,000,000-mile coolant when properly maintained
- Cummins and OEM approved Nitrite, Amine, Phosphate, and Silicate free formulation
- Provides antifreeze and antiboil protection
- Superior liner pitting and corrosion protection
- Superior aluminum and solder protection
- 2-ethylhexanoic acid free formula is compatible with all system gasket and hose materials
- Optimizes cooling system performance and water pump life
- Contains proprietary scale inhibitors

## Valuable Versatility:

- Compatible with all other antifreeze/coolants
- Available in concentrate, 50/50 and 60/40
- For all diesel, gasoline and natural gas engines

## Simple Serviceability:

- Low maintenance coolant with no SCA addition
- Compatible with chemical-free ES water filters



	OAT EG Concentrate	OAT EG PreMix 50/50	OAT EG PreMix 60/40
<b>Bulk</b>	* CC36070	* CC36074	CC2908
<b>275 Gallon Plastic Tote (1040 L)</b>	CC36070USR	CC36074USR	CC2908USR
<b>55 Gal. Drum (208 L)</b>	CC36072	CC36076	CC36078
<b>3/1 Gal. Bottle (3.78 L)</b>	CC36073 CC36073X (Canada Only)	CC36077 CC36077X (Canada Only)	

\* Currently available in US only

## Specifications

Specification	Performance Standard	OAT Concentrate	OAT Premix 50/50	OAT Premix 60/40
Color	Visual	Red	Red	Red
Specific Gravity @ 60° F (15.56° C)	D1122	1.130	1.070	1.090
Density	-	9.43 lb/gal (1.13 kg/L)	8.93 lb/gal (1.07 kg/L)	9.07 lb/gal (1.09 kg/L)
pH (undiluted)	D1287	8.6	8.6	8.6
Reserve Alkalinity (undiluted)	D1121	9.3	4.6	5.5
Freeze Point (undiluted)	D1177	8° F (-13.33° C) min.	-34° F (-36.67° C) min.	-65° F (-53.89° C) min.
Boiling Point (undiluted)	D1120	338° F (170.00° C) min.	226° F (107.78° C) min.	230° F (110.00° C) min.
Water by Weight (approx.)	D1123	4.0%	47.0% max.	37.0% max.
Total Glycol by Weight	-	95.0% min.	51.0% min.	61.0% min.
Glassware Corrosion Test	D1384	Pass	Pass	Pass
Aluminum Corrosion Test	D4340	Pass	Pass	Pass
Simulated Service Test	D2570	Pass	Pass	Pass
Aluminum Water Pump Test	D2809	Pass	Pass	Pass
Silicates	-	None	None	None

Check out our video “How to Use Fleetguard 4-Way Coolant Test Strips” <https://bit.ly/2RxcEIA>

## Monitor Your Cooling System

These quick and accurate tools are all you need:

- Dip and read test strips to easily test your coolant and water
  - Test freeze point and additive levels (CC8997)
  - Test glycol and water quality (CC2609 & CC2718)
- Refractometers (CC8998) that easily determine freeze point
- Monitor™ Coolant Analysis (CC2700) for when more detailed analysis is required – recommended 1x / year

CC8997



WF2121



DCA60L



CC2700

