



# ES Compleat™ EG

Lifetime Heavy-Duty Fully Formulated Antifreeze/Coolant

## Proven Performance:

- Life-of-the-Engine, 1,000,000 miles
- Provides antifreeze and antiboil protection
- Superior liner pitting and corrosion protection
- Exceeds ASTM D6210 and ASTM D3305
- CES14603 and CES14439 approved
- Compatible with gaskets, hoses and other non-metallics in the cooling system
- Optimizes cooling system performance and water pump life
- Contains proprietary scale inhibitors

## Valuable Versatility:

- Compatible with other antifreeze/coolants
- Available in concentrate, 50/50 and 60/40
- For all heavy-duty diesel and gas engines

## Simple Serviceability:

- Provides 20,000 hours of protection
- Maintain with liquid DCA-4 or chemically active water filters as needed



ES Compleat EG	EG Concentrate	EG PreMix
<b>Bulk</b>	CC2822	CC2827
<b>275 Gallon Plastic Tote (1040 L)</b>	CC8984	CC8983
<b>275 Gallon Plastic Tote (1040 L)</b>		CC2907USR <sup>60/40</sup>
<b>55 Gallon Drum (208 L)</b>	CC2821	CC2826
<b>55 Gallon Drum (208 L)</b>		CC2863 <sup>60/40</sup>
<b>5 Gallon Pail (19 L)</b>	CC2847	CC2848
<b>6/1 Gallon Bottle (3.78 L)</b>	CC2820, CC02820X (Canada Only)	CC2825, CC02825X (Canada Only)

Fleetguard coolant part numbers apply to both U.S. and Canada, except where separate part numbers are noted.

Specification	Performance Standard	EG Concentrate	EG Premix 50/50	EG Premix 60/40
Color	Visual	Blue	Blue	Blue
Specific Gravity @ 60° F (15.56° C) @ 68° F (20° C)	D1122 D1122	1.13	1.072 1.070	1.084 1.082
Density	–	9.43 lb/gal (1.13 kg/L)	8.944 lb/gal (1.072 kg/L)	9.044 lb/gal (1.084 kg/L)
pH (undiluted)	D1287	10.5	10.0	10.5
Reserve Alkalinity Typical (undiluted)	D1121	13.3	6.6	8.0
Freeze Point (undiluted)	D1177	8° F (-13.33° C) min.	-35.8° F (-37.68° C) min.	-54° F (-47.78° C) min.
Boiling Point (undiluted)	D1120	330° F (165.56° C)	226° F (107.78° C)	231° F (110.56° C)
Water by Weight (approx.)	D1123	4.0%	48.99% max.	40.18%
Total Glycol by Weight	–	95.0% min.	50.19% min.	58.87%
Glassware Corrosion Test	D1384	Pass	Pass	Pass
Water Pump Cavitation Test	D2809	Pass	Pass	Pass
Aluminum Corrosion Test	D4340	Pass	Pass	Pass
Simulated Service Test	D2570	Pass	Pass	Pass
Ash Content by Mass	D1119	1.8%	0.9%	1.1%
Chloride by Weight	D5827	< 25 ppm	< 25 ppm	< 25 ppm

Check out our video “How to Use Fleetguard 3-Way Coolant Test Strips” <https://bit.ly/2vPOBN3>

## Monitor Your Cooling System

These quick and accurate tools are all you need:

- Dip and read test strips to easily test your coolant and water
  - Test freeze point and additive levels (CC36050)
  - Test water quality and coolant condition (CC2602 & CC2718)
- Refractometers (CC36049) that easily determine freeze point
- Monitor™ Coolant Analysis (CC2700) for when more detailed analysis is required – recommended 1x / year

CC2602



CC2718



CC36049



CC2700

