



Performance Data Sheet

AF25149NF

NanoForce™ Radial Seal Air Filter for SSG Housings

Description

Fleetguard® NanoForce™ air filters deliver the cleanest combustion air for large construction and mining engines and equipment. The new AF25149NF continues the application of this filter media for premium levels of protection. The nanofiber media applies the enhanced filter media pleating and pleat stabilization to deliver superior engine protection and long filter service life.

Features

- **Nanofiber filter media** provides the highest possible engine protection efficiency without compromising filter life
- **Pleat geometry, spacing and stabilization** yields maximum filter performance and long life for lower equipment operating costs
- **Proven radial air filter seal** ensures reliable fit in the SSG air housing and easy service events
- **Complete Fleetguard system solution** including the AF25150 secondary filter and the SP1307 housing service cover

3X the engine protection
versus conventional filters



AF25149NF Specifications

Capacity	8,778 g (with nominal 0-5 micron dust) 15,978 g (with ISO fine test dust)
Rated Air Flow	2,400 ft ³ /min (67.9 m ³ /min)
Efficiency	99.99% (with 0-5 micron dust per ISO 5011)
Seal Type	Radial on open end (fits SSG radial seal air housings)
Outside Diameter	17.7" (449.0 mm)
Inside Diameter	11.5" (293.0 mm)
Overall Height	29.54" (750.36 mm)
Secondary Air Filter (if required)	AF25150

Applications

- Off-highway mining only
- CAT 789D, 794 AC, 797F, MT5300D AC Haul Trucks, Liebherr T282 Haul Truck, and others

Installation and Use Tips

- Use of the AF25149NF filter requires the use of the SP1307 air housing service cover and the AF25150 secondary air filter.
- Fleetguard® air filters must be used as sets. The OE air filters and air housing cover are not compatible with the Fleetguard filters and cover.
- Use an air filter restriction measuring device to determine when to change the used air filter.
- Do not disturb the air filter until an air filter restriction measurement indicates that the filter should be serviced, typically at 25" H₂O restriction (6.23 kPa or 0.063 bar).
- Use caution when lifting used air filters. The dust capacity (~7,000 g (~15.4 lb)) for a plugged filter plus the filter weight can make the filter heavy to handle.
- Ensure that no dust or debris is allowed to enter the clean side of the filter housing.
- Do not disturb the secondary filter element unless it needs to be changed. The secondary air filter should be changed approximately every third primary element change.
- Follow OE recommendations for properly cleaning and servicing air housing pre-cleaners.



For more detailed information or to find the nearest retailer of Fleetguard products, visit cumminsfiltration.com/wrl.



For more information, visit cumminsfiltration.com

PD10022 Rev2
©2017 Cummins Filtration Inc.
Printed in USA on Recycled Paper